



TECHNICAL DATA SHEET

Oregon 2T Oil

PRODUCT DESCRIPTION

This high-quality two-stroke oil contains active cleaning agents and corrosion-preventive ingredients and is suitable for mixed and separate lubrication of air and water-cooled two-stroke engines of all brands. Miscibility at a ration of up to 1:50.

The advantages of Oregon 2T Oil:

- + Allows a smooth and swift engine start, even after long periods of storage
- + Protects against corrosion and wear
- + Keeps the fuel system clean
- + Self-mixing

CHARACTERISTICS

Appearance	rot
Viscosity/40°C / ASTM D 7042	56 mm ² /s
Viscosity/100°C / ASTM D 7042	9.4 mm ² /s
Viscosity index / ASTM D 2270	155
Density/15°C / DIN EN ISO 12185	0,859 g/cm ³
Pour point / DIN ISO 3016	< -30°C
Flash point (Cleveland) / DIN ISO 2592	>80 °C

4830BB

05/2019-4830BB-0

The statements made in this publication are according to our present knowledge. They do not absolve the user from own examinations. A legally binding assurance of certain properties or suitability for a specific use can not be derived from our statements. Possibly existing laws and regulations concerning the handling and use of our products have to be observed by the receiver of our products himself.



TECHNICAL DATA SHEET

Oregon 2T Oil

SPECIFICATION

API TC; JASO FD; ISO-L-EGD

APPLICATION

Oregon 2T Oil can be used just like normal two stroke oils. Suitable for chain saws, two-stroke lawn mowers, scooters etc. in mixing ratios up to 1:50 (please see the manufacturer's requirements!).

Benefit from our service, we will gladly advise you and develop individual application recommendations for your process. Please also note the material safety data sheet.

4830BB

05/2019-4830BB-0

The statements made in this publication are according to our present knowledge. They do not absolve the user from own examinations. A legally binding assurance of certain properties or suitability for a specific use can not be derived from our statements. Possibly existing laws and regulations concerning the handling and use of our products have to be observed by the receiver of our products himself.

2 / 2